



# TECHNICAL DATA SHEET

## NOVBELT 250 HC 2,5/2000 BLACK

PRODUCT NUMBER: 9914102

### TECHNICAL SPECIFICATIONS:

CHARACTERISTIC	MEASURE UNIT	VALUE	CONTROL METHOD
Area weight	g/m <sup>2</sup>	1400 ± 150	
Thickness	mm	2,6 ± 0,15	
Breaking strength L	N/mm	110 ± 30	ISO 283
Elongation L	%	20 ± 4	ISO 283
Tensile strength at 1,0% el.	N/mm	15 ± 3	ISO 283
Electrical surface resistances	Ω	< 1x10 <sup>7</sup>	ISO 21178 (Method A)
Electrical volume resistances	Ω	< 1x10 <sup>7</sup>	ISO 21178
Coefficient of friction in fiber direction	μ	0,19 ± 0,06	ISO 21182
Air permeability at 200 Pa	l/dm <sup>2</sup> .min	12 ± 5	ISO 9237
Minimum pulley diameter	mm	30	
Back flexing min diameter	mm	60	
Width	mm	2000	
Length of the roll	m	210	
Temperature resistance	°C	-20 / +120	

DATE: 20.06.2023

*Please note value given may be subject to change without notice.*

*Consult Konus Konex before using these values for design or specifications.*

*Please note this data sheet will supersede any previous version.*

### KONUS KONEX d.o.o.

Mestni trg 18, SI-3210 Slovenske Konjice, Slovenia, EU

T: +386 3 757 3 100, E: novbelt@konuskonex.com, info@konuskonex.com

www.novbelt.com, www.konuskonex.com

NOVBELT